

ASSEMBLY DRAWING

MODEL #:6J2GASWC

1. ASSEMBLE THREE TOP PLANKS TOGETHER BY ATTACHING THE LONG END CAPS TO PLANKS W/ DRIVE SCREWS.
2. PLACE THE TOP ASSEMBLY ON A NON MARKING SURFACE (SOLID SIDE DOWN). MEASURE 9" (FOR 6' TABLE) OR 15" (FOR 8' TABLE) FROM ONE END OF TABLE. PLACE ONE LEG ON THE PLANKS WITH HOLES FACING THE CENTER OF THE TABLE. PUT THE HOLD DOWN CLIPS IN PLACE USING THE 5/16" CARR. BOLTS. HAND TIGHTEN AT THIS TIME.
3. MEASURE 54" (6' TABLE) OR 66" (8' TABLE) DOWN THE TABLE FROM THE FIRST SET OF HOLES AND PLACE THE OTHER LEG ON THE PLANKS. MAKE SURE THE HOLES ALSO FACE THE CENTER. HAND TIGHTEN WITH SAME HARDWARE AS ABOVE.
4. BOLT ONE OF THE SHORT BRACES TO THE FIRST LEG SPACER USING 1 1/4" HEX BOLT. THEN BOLT A CENTER CLEAT TO THE OTHER END OF THE BRACE W/ 3/8" NUT. NOW BOLT THE CLEAT TO THE PLANK W/ HOLD DOWN CLIPS. REPEAT FOR THE OTHER BRACE.
5. RECHECK HOLE SPACE DIMENSION (54" ON 6' OR 66" ON 8') AND END DIMENSION (9" ON 6' OR 15" ON 8'), MAKE SURE LEGS ARE VERTICAL, THEN TIGHTEN ALL BOLTS. ONCE TIGHT, TURN TABLE OVER.
6. ATTACH END CAPS ONTO REMAINING PLANKS USING DRIVE SCREWS.
7. ATTACH LONG PLANK ON LEG SEAT CLEATS EVEN W/ THE LEFT END OF TOP PLANKS USING HOLD DOWN CLIPS.
8. ATTACH THE TWO SEAT SUPPORT PLATES TO THE SEAT CLEATS W/ 1 1/4" HEX BOLTS. SEE FIGURE BELOW.
9. ATTACH THE TWO 16" SEAT PLANKS TO THE SEAT SUPPORT PLATE W/ CARR. BOLTS. SEE FIGURE BELOW.

TOP VIEW OF LEFT HAND 16" SEAT PLANK



THE HOLES LINE UP AS SHOWN HERE. OUTSIDE HOLES USED TO ATTACH PLANK TO SEAT PLATE.

SEAT SUPPORT PLATE

SEAT CLEAT ON THE TABLE LEG

INSIDE HOLES USED TO ATTACH SEAT PLATE TO SEAT CLEAT.

TOP VIEW OF RIGHT HAND 16" SEAT PLANK



SEAT SUPPORT PLATE

THE HOLES LINE UP AS SHOWN HERE

SEAT CLEAT ON THE TABLE LEG

