

Detail of Seat Mounting Bracket

- 2. Attach the table legs, one at a time, to the sides of the support bars in the table top. Use a 3/8" x 2 3/4" hex bolt with a flat washer on each side and a locknut. Be sure that each lea
- is on the same side of each support bar as you go around the table.
- 3. Bring a leg up to the lower ring. Line up the hole in the leg with one of the channels/hole in the lower ring and attach it using a 2 3/4" hex bolt and lock nut.
- 4. Now bring the rest of the legs up, one at a time and attach to the lower ring the same way as step 3. Place the umbrella bracket on the inside of the lower ring. Attach it using the same bolt that goes through the leg. Pick the leg directly opposite of the leg you just used for the umbrell bracket and place the other end of the umbrella bracket on the same way. Use 3/8" x 23/4" hex bolt and locknut for all of the legs.
- 5. Attach the seats to the sides of the seat mounting angles on the legs with two 1 1/2" hex bolts with flat washers on each side and locknuts per leg. (Four bolts per seat)
- 6. Tighten all the bolts. Place some packing cardboard under the seat and 2 leas where they will touch the ground. Then turn the entire assembly right side up (2 people are needed for this).

## **FURNITURE LEISURE INC**

OUR LIST OF WEB STORES

www.ParkTables.com

www.FoolFurnitureSupply.com www.PicnicFurniture.com www.PicnicTableSupplier.com

1.800.213.2401

RTRCFVPS **Assembly Instructions**