

Model # T8INNV 3/4/2019 Page 1 of 8

# HARDWARE 5/16" x 1" Machine Bolt 5/16" Washer 5/16" Kep Nut

3/4/2019 Page 2 of 8

### PRODUCT SPECIFICATIONS

### T8INNV 8' PICNIC TABLE WALK-THROUGH DESIGN

Top & Seats: 11 gauge die formed angle frame 1"x1-7/8" with 3" radius corners. Seat and top plates are fabricated from a 12ga plate. Holes are precision punched at 5/8" diameter. 7 gauge x 1-1/2" flat bar center support and mounting bracket understructure. Electrically MIG welded.

Coating: Oven fused functionalized polyethylene copolymer-based thermoplastic. Fluidized bed coating application with superior mechanical performance, impact resistance and UV-stability.

Frame: 2-3/8" O.D. x 12 gauge pre-galvanized structural steel tubing. Cross braces 1" O.D. x 16 gauge pre-galvanized structural steel tubing. Brace attachment points 1-1/2"x1-1/2"x3/16" steel angle. Seat and top mounting points 7 gauge x 1-1/2" die stamped steel flat bar. Legs are bent over a mandrel through the bend radius producing a wrinkle free bend. All electrically MIG welded.


Frame Coating: Electrostatic powder coated application oven cured.

Hardware: All stainless steel hardware fasteners.

Dimensions: 8' portable picnic table walk-through design. Top is 30" wide x 96" long and is 30-1/4" high. Seats are 12" wide x 96" long and 18-1/2" high. Outside to outside dimension is 68-1/2" x 96".

3/4/2019 Page 3 of 8


## COMPONENTS



ITEM NO.	PartNo	DESCRIPTION	QTY
1	T-P96-S	8' Punched Seat	2
2	T-P96-T	8' Punched Top	1
3	P-01-04-0125	29 7/8" Brace	2
4	P-V238	238 Vinyl Frame	2
5	33-02-0007	5/16" SS Washer	40
6	33-05-0029	5/16" x 1" Machine Bolt (SS)	20
7	33-03-0012	5/16" Kep Nut (SS)	20

3/4/2019 Page 4 of 8


# STEP 1



Attach the 8' Punched Top to the Frames using specified hardware.

3/4/2019 Page 5 of 8


### STEP 2



Attach the 29-7/8" Braces to the 8' Punched Top and the Frames as shown using specified hardware.


3/4/2019 Page 6 of 8

## STEP 3



Attach the 29-7/8" Braces to the 8' Punched Top and the Frames as shown using specified hardware.

3/4/2019 Page 7 of 8



3/4/2019 Page 8 of 8